

POLYFLOR BEVEL LINE WOOD PUR

- Captures the natural beauty of wood
- Authentic reproductions of real materials
- Design accessories available upon request

SPECIFICATION



2.5mm



0.7mm



bevelled edges



36 @ 101 x 914mm
= 3.34m²



4290g/m²



GENERAL PERFORMANCE

EN 649
EN ISO 10582



REACTION TO FIRE
EN 13501-1 Class Bfl-S1



SLIP RESISTANCE
EN 13893 Class DS (dry condition)*
DIN 51130 R10
AS/NZS 4586 R10

For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges



LIGHT FASTNESS
ISO 105-B02 Method 3 ≥6



ABRASION RESISTANCE
EN 649 Group T
EN ISO 10582 Type 1



INDENTATION - RESIDUAL
EN 433 ≤ 0.05mm
EN ISO 24343-1 ≤ 0.05mm



DIMENSIONAL STABILITY
EN 434 ≤ 0.1% max.
EN ISO 23999 ≤ 0.1% max.



CASTOR CHAIR (continuous use)
EN 425 / ISO 4918 Suitable



THERMAL CONDUCTIVITY
Suitable for underfloor heating Max. 27°C



VOC EMISSIONS

Indoor Air Comfort GOLD - Eurofins certified product
AgBB - Very low emissions
FloorScore - Certified product



ENVIRONMENTALLY PREFERABLE FLOORING

Polyflor Bevel Line PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429) in major use areas such as education, healthcare and retail. Bevel Line PUR is 100% recyclable and contains average 40% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



Bevel Line PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention.



APPLICATIONS

Bevel Line is ideal for all residential areas and heavy commercial areas such as hotels, offices, schools, hospitals, airports and department stores.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

At the date of issue the data presented is correct.

* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



2011



BEVELline™
THE WOOD & STONE COLLECTION

WOOD



PERFORMANCE AND
PROPERTIES

A+BRE
ENP 429
ENVIRONMENTAL
RATING
Refer to BRE Global ratings
on www.greenbooklive.com



POLYFLOR™
COVERING THE WORLD