

## POLYFLOR COLONIA PU

- Colonia - collection of residential vinyl floor products
- Stone, slate and marble effect floorcovering designs
- Coordinating inlay strips to blend, shape or accentuate design ideas

### SPECIFICATION



2.0mm



0.2mm



36 @ 305 x 305mm = 3.34m<sup>2</sup>  
16 @ 457 x 457mm = 3.34m<sup>2</sup>  
18 @ 610 x 305mm = 3.34m<sup>2</sup>



3680g/m<sup>2</sup>



#### GENERAL PERFORMANCE

EN 649  
EN ISO 10582



#### REACTION TO FIRE

EN ISO 13501-1 Class Bfl-S1



#### SLIP RESISTANCE

EN 13983 Class DS  
DIN 51130 R10

For safety flooring with sustainable wet slip resistance, refer to the Polysafe ranges



#### ABRASION RESISTANCE

EN 649 Group T  
EN ISO 10582 Type 1



#### INDENTATION - RESIDUAL

EN 433 ≤ 0.1mm



#### DIMENSIONAL STABILITY

EN 434 ≤ 0.25% max.



#### THERMAL CONDUCTIVITY

Suitable for underfloor heating Max. 27°C



**CASTOR CHAIR**  
(continuous use)  
Suitable



#### LIGHT FASTNESS

ISO 105-B02 Method 3 ≥ 6



#### VOC EMISSIONS

**Indoor Air Comfort GOLD** - Eurofins certified product  
**AgBB** - Very low emissions  
**FloorScore** - Certified product



#### ENVIRONMENTALLY PREFERABLE FLOORING

Polyflor Colonia PU achieves a BRE Global Environmental A Rating (Certificate No: ENP 429). Colonia PU is 100% recyclable and contains 15% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/environment](http://www.polyflor.com/environment)



#### APPLICATIONS

Colonia PU is ideal for general domestic use.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

\* For clarification regarding slip resistance, consult Polyflor.

**VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR**



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

*James Hallett*  
FLOORING




2011

COLONIA™  
FLOORING COLLECTION

STONE

PERFORMANCE AND  
PROPERTIES

**A BRE**  
ENP 429  
ENVIRONMENTAL  
RATING  
Refer to BRE Global ratings  
on [www.greenbooklive.com](http://www.greenbooklive.com)



**POLYFLOR™**  
COVERING THE WORLD