

POLYFLOR CLASSIC MYSTIQUE PUR



2.0mm



2m x 20m = 40m²



300 x 300mm = 4.5m²
608 x 608mm = 5.17m²



3250g/m²



GENERAL PERFORMANCE
EN 649 / EN ISO 10581
ASTM F1913
ASTM F1700



REACTION TO FIRE
EN 13501-1 Class Bfl-S1
ASTM E662 <450
ASTM E648 Class 1



SLIP RESISTANCE
EN 13893 Class DS
AS/NZS 4586 R9



ABRASION RESISTANCE
EN 660-2 Group P
EN ISO 10581 Type I



ELECTRICAL BEHAVIOUR (body voltage)
EN 1815 ≤2kV
Classified as 'antistatic'



VOC EMISSIONS
Indoor Air Comfort GOLD Eurofins certified product
AgBB VOC test: Pass
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)
Finnish M1 Classification: Pass
Swedish B.P.D (FLEC test): Best Class
GBCA/NZGBC Green Star IEQ-VOC: Compliant



CASTOR CHAIR (continuous use)
Suitable



INDENTATION RESIDUAL
ASTM F970 (Modified)
Static load 750psi



ENVIRONMENTALLY PREFERABLE FLOORING
Polyflor Classic Mystique PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Classic Mystique PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



AGRÉMENT ASSURANCE
Polyflor Classic Mystique PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



HYGIENE
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polyflor Classic Mystique PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS
Polyflor Classic Mystique PUR is recommended for heavy traffic areas that require a homogeneous floorcovering that offers durability, reliability, ease of maintenance and aesthetic appeal. Ideally suited for the most demanding of areas within the Healthcare and Education sector, as well as Retail, Leisure and the Commercial environment.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Hallett Ltd
FLOORING



2011



POLYFLOR
CLASSIC MYSTIQUE PUR
HOMOGENEOUS




PERFORMANCE AND PROPERTIES



Refer to BRE Global ratings on www.greenbooklive.com



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).



HOMOGENEOUS