



OCTOBER

2012

Frontrunner Entrance Flooring System





FRONTRUNNER: THE ELEGANT, FLEXIBLE AND HIGH QUALITY ENTRANCE FLOORING SYSTEM FROM PLASTEX



The second

A REAL POINTS OF THE PROPERTY OF T

1

6470

医治疗学生的治疗 化加加加加分配的 化化化化化化化化化化化化化化化化化化化化化化化化化化化化

为17. 大学的学校的是中国的学校的学校,在学校的学校中的学校,如此是自己的学校和自己的学校的学校。在13世纪中的学校的学校中的学校。

i



With manufacturing sites in the UK and the US, Plastex is a well-established, global family run business specialising in the design and production of a wide range of matting products combining good looks, exceptional quality and outstanding



performance. Our range of matting has been tested and certified to many international legislative and safety

We also have a strong environmental ethic, and look at ways of reducing environmental impact wherever we can. Our entrance flooring product grids are

made from vinyl that is 100% recyclable, and our

black grids can be made from post industrial recycled material. The materials we use are CFC free, and do not contain heavy metals or brominated flame retardants as per Directive 2002/95/EC. We also comply with REACH regulations Directive EC 1907/2006 - Annex I.

Over the last 50 years of business, we have developed an extensive range to cover most applications but we never forget the importance of the personal touch. We are more than happy to work with specifiers and architects to develop solutions to meet exact needs. In fact we first made some of the products you'll see in this brochure to a specific client brief, so if you have any questions please don't hesitate to get in touch.

FRONTRUNNER ENTRANCE FLOORING SYSTEM

Flexible vinyl matting manufactured in rolls for ease of installation and to provide large one piece covering. Also available in cut to size format or with factory fitted edges for surface mounted applications.



Choosing the right entrance flooring matters for three good reasons:

- Style
- Health and Safety
- Cleanliness and durability

Style

Your entrance flooring is, by definition, one of the first things clients and visitors see; so it plays a vital role in creating first impressions. As you'll see from the location pictures in this brochure our range of colours, custom logos, styles and tread patterns will make sure you get it right.

Health and safety

Unfortunately we live in a litigious age. That's why it's good to know the Frontrunner Entry and Frontrunner XT are classified R11 under DIN 51130. This means they have been tested to be slip resistant at an angle of 27°, even when wet. This translates to peace of mind that your entrance flooring system is independently tested giving a performance safe entrance flooring. Additionally, the Frontrunner Entrance Flooring System conforms to the requirements of the BS 8300:2009 Design of buildings and their approaches to meet the needs of disabled people. Code of Practice.

Cleanliness and durability

Up to 80% of dirt comes into your building on shoes or wheels. All Frontrunner entrance flooring is designed to remove, trap and hide this dirt from the traffic areas until it is easily removed during cleaning.

Our flooring deals with dirt so effectively that it will expand the life of your internal floor finishes and will help reduce your cleaning intervals. Frontrunner's one piece welded roll format ensures a durable and effective product. For further peace of mind, many of the installations shown in this brochure have been in place for ten years or more and still look as good as the day they were fitted.

WHY FRONTRUNNER ENTRANCE FLOORING SYSTEM?

- 100% recyclable and REACH^{*} compliant vinyl grid
- Meets the requirements of the UK Disability Discrimination Act BS 8300:2009
- Excellent Fire rating EN 13501 1 : 2007- Bfl S1 available as premium specified grade
- Available in rolls for seamless quick and easy installations
- Loose lay open grid construction removes dirt from traffic area and eases cleaning
- RII slip resistance rating under DIN 51130 on Frontrunner Entry and Frontrunner XT
- Frontrunner Plus available in over 80 different colour combinations. Can also be customised with the incorporation of a logo panel



ISO 9001 accredited (since 1993) ensures quality entrance flooring systems that are fit for purpose.



Founder Member

Directive EC 1907/2006 – Annex I



 Registration, Evaluation, Authorisation and restriction of CHemical substances.

WHICH FRONTRUNNER ENTRANCE FLOORING SYSTEM IS RIGHT FOR YOU?

The Frontrunner Entrance Flooring System includes flooring products ideally suited for both external and internal use. With families of products available in equal height, a smooth and quiet transition throughout the entrance area is achieved. The chart below will help you choose the right combination for your application, but if you have any questions contact us we'll be delighted to help.

PRODUCT	FRONT/ SIDE ELEVATION	SLIP RESISTANCE	SCRAPER	MOISTURE REMOVAL	LOCATION (See opposite)	USAGE
VIN	(L OPEN GRI	D CONSTRI	JCTION - PRIM	ARY MATTI	NG	
Frontrunner Entry Frontrunner Entry Low Profile p. 6-7	SIDE FRONT	ጙጙጙጙ			B	High traffic internal areas.
Frontrunner XT p. 9	SIDE FRONT	ጙ፞ጙ፞ጙ፞ጙ፞	anna anna anna anna		(also ideal for walkways, balconies and decking)	High traffic internal/externa areas.
VINYL OPEN GF	-	UCTION WI	TH BRUSH INSE	RTS - PRIM	1ARY M	ATTING
Frontrunner Brush p. 10		ጙ፞ጙ፞ጙ፞ጙ፞	numero numero numero numero		A	Maximum dirt removal in internal/externa areas.
Frontrunner Brush Wide p.		ጙ፞ጙ፞ጙ፞ጙ፞	TINTER TINTER TINTER TINTER		A	Larger debris removal in external areas
VINYL OPEN GR	ID CONSTRUC	TION WITH A	BSORBENT INSER	TS - SECONI	DARY MA	ATTING
Frontrunner Plus Frontrunner Plus Low Profile p. 14-15		ጙጙጙጙጙ			BC	Maximum moistu removal in high traffic internal areas.
VINYL OPEN R	IBBED CONST	RUCTION WI	TH A SOLID BACK	- SECONDA	RY MAT	TING
Frontrunner SB p. 8	SIDE FRONT	ጙጙጙጙጙ	nunter nunter nunter		В	Surface mounted high traffic intern areas.
Frontrunner SB+ p. 17	SIDE FRONT	ጙጙጙጙጙ	um & um &		BC	Surface mounted moisture remova in high traffic internal areas.
		and the second				



The original 'scrape and clean' entrance system



DARK GREY

HOLLY GREEN

Standard colours







BLACK




For modules and ancillary range see pages 20 & 21

PRODUCT	HEIGHT	WEIGHT	STAN	NDARD ROLL SI	ZES
Frontrunner Entry	I4mm	10.5 kg/m ²	10m x 60cm	10m x 91cm	5m x 120cm
Frontrunner Entry Low Profile	10mm	8.7 kg/m ²	10m x 60cm	10m x 91cm	5m x 120cm
To ensure maximum flexibility and	d convenience	, Frontrunner En	trance System can	be delivered in ro	olls or cut to

To ensure maximum flexibility and convenience, Frontrunner Entrance System can be delivered in rolls or cut to size - ask your salesperson for details. For full technical information, see pages 22-23.

Scrape and clean Roll format Frontrunner Entry is uniquely effective in helping for one piece prevent dirt from entering buildings. Its aggressive large area diamond tread pattern scrapes dirt off shoes, whilst coverage the open grid structure allows it to fall out of the way. -With practicality in mind, the matting is specially Loose lay open grid designed to present no problems to high heels or small I vinyl construction wheeled traffic. Frontrunner Entry can be used in M combination with other products from the Frontrunner Certified high slip Entrance Flooring System range for a complete interior resistance DIN 51130 R11 A N P. BENEF and exterior entrance matting solution. It is available in standard 14mm grid height and also in low Heel & wheel profile 10mm height, which enables it to fit quickly and Available in proof system seamlessly with current flooring. 14mm & 10mm heights Slip Resistance Test Results DIN 51130 RII, VIO



Frontrunner Entry

Frontrunner Entry Low Profile

FRONTRUNNER SB



Frontrunner SB

Surface mounted 'scrape and clean' entrance flooring system

Frontrunner SB is the perfect flooring solution for applications that require an entrance matting but do not have a recessed matwell. Its 6mm overall height and solid backing allow it to deliver this.

Frontrunner SB's ribbed pattern scrapes dirt off shoes, which is effectively contained by its solid back. The hollow ribbed construction makes it light to handle during installation, yet sturdy enough to be heel and wheel proof.

Due to Frontrunner SB's lesser overall weight, we recommend adhering it to the sub-floor in high volume traffic areas.

Standard colours



PRODUCT	HEIGHT	WEIGHT	STANDARD F	ROLL SIZES
Frontrunner SB	6mm	6.3 kg/m ²	10m x 1m	20m x Im

To ensure maximum flexibility and convenience, Frontrunner Entrance System can be delivered in rolls or cut to size - ask your salesperson for details. For full technical information, see pages 22-23.



FRONTRUNNER XT

Extra grip for exterior applications

Frontrunner XT works just as effectively as Frontrunner Entry but its extra certified grip makes it suitable for outdoor areas that may become more hazardous through exposure to the elements.

It provides an ideal solution for external areas such as walkways and decking, keeping visitors and staff safe in all weathers. Frontrunner XT can be used in combination with Frontrunner Brush and Frontrunner Plus, providing a complete system that initially removes underfoot dirt before entering, and then scrapes, cleans and dries when inside.

Roll format for one piece large area coverage

 Loose lay open grid vinyl construction

 Effectively removes debris

A'N BENEFI Certified high slip resistance

Standard colours



DARK GRE

PRODUCT	HEIGHT	WEIGHT	STA	NDARD ROLL	SIZES
Frontrunner X	T I4mm	10.5 kg/m ²	10m x 60cm	10m x 91cm	5m x 120cm

To ensure maximum flexibility and convenience, Frontrunner Entrance System can be delivered in rolls or cut to size - ask your salesperson for details. For full technical information, see pages 22-23.


Slip Resistance Test Results


I

1

DIN 51130 RII, VIO

DIRECTION OF TRAFFIC






Heel & wheel proof

system

T S

Frontrunner XT



Heavy duty external system

- nylon 6.6 brush inserts
- Effective moisture 5 and dirt removal
- Roll format for one piece large area coverage
- Loose lay open grid vinyl construction



- High quality
- &⁴/
- MAIN


FRONTRUNNER BRUSH

For maximum moisture and dirt removal

Frontrunner Brush, as the name implies, has additional brush strips with bristles that scour snow, mud and other heavy contaminants from the shoe, boot or wheel. High quality nylon 6.6 brushes ensure durability and continued effectiveness.

Once again the mat's primary use is external, keeping buildings dirt-free under the most extreme conditions. Frontrunner Brush works as a 'stand alone' module or in combined use with other Frontrunner Entrance Flooring Systems.

PRODUCT	HEIGHT	WEIGHT	STAN	IDARD ROLL	SIZES
Frontrunner Brush	h I9 mm	12.7kg/m ²	10m x 60cm	10m x 91cm	5m x 120cm
To ensure maxin delivered in rolls		,			ystem can be






Standard colours





BLACK



FRONTRUNNER BRUSH WIDE

Wider grid allows larger debris to fall through


Frontrunner Brush Wide completes the Frontrunner exterior range. With similar properties to Frontrunner Brush, but with a wider grid that allows larger debris such as small stones to fall through and be contained. Applications where Frontrunner Brush Wide comes into its own are during the icy/snowy winter months, in areas with a lot of gravel or small stones, salted areas, beaches or shingle. It works either as a stand alone or can be swapped with another Frontrunner system in summer months to provide the complete entrance solution.

PRODUCT	HEIGHT	WEIGHT	STAN	NDARD ROLL	SIZES
Frontrunner Brush Wide	19mm	7.5kg/m ²	10m x 60cm	10m x 91cm	5m x 120cm
To ensure maximum flexibility and convenience, Frontrunner Entrance System can be delivered in rolls or cut to size - ask your salesperson for details.					




Standard colours






BLACK



SHOWN ACTUAL SIZE: SIDE ELEVATION

DIRECTION OF TRAFFIC



Frontrunner Brush Wide




Vinyl Entrance Flooring System for high traffic areas

Specified worldwide for:

• Hotels • Hospitals • Industrial sites • Leisure facilities

CHINE

- Office/banks Public buildings
- Restaurants Retail locations
- Schools Supermarkets



The all-in-one 'scrape clean and dry' entrance flooring system

25155

For grid colours and carpet colour combinations see pages 18-19

For modules and
ancillary range
see pages 20 & 21

				ES
16mm 10.5	kg/m ² I0m x	60cm 10m	x 91 cm 5r	m x I20cm
12mm 8.7 k	kg/m² I0m x	60cm 10m	x 91 cm 5r	m x I20cm
	12mm 8.7 k	12mm 8.7 kg/m ² 10m x	12mm 8.7 kg/m ² 10m x 60cm 10m	

To ensure maximum flexibility and convenience, Frontrunner Entrance System can be delivered in rolls or cut to size - ask your salesperson for details. For full technical information, see pages 22-23. Internationally acclaimed for its outstanding performance, Frontrunner Plus, with its unique duo of benefits, keeps internal floors clean and dry by removing both moisture and dirt from shoes and wheels as they enter buildings. It is a truly superior all-in-one interior entrance flooring system.

By using Frontrunner Plus alone, or with other Frontrunner products, even the busiest pedestrian traffic flow areas will look their best, whilst internal floorings remain protected thus reducing cleaning costs. Purpose designed for interior use, Frontrunner Plus is both slip resistant and wheelchair friendly. A choice of over 80 colour combinations offers the exact mix of aesthetic elegance and superior performance.


Available in standard 14mm grid height and also in low profile 10mm height, which allows it to fit quickly and seamlessly with current flooring.

- Specially formulated absorbent inserts
- Heel & wheel proof system
- Available in
 14mm & 10mm
 heights

1

- Loose lay open
 grid vinyl construction
 - Flexible vinyl for ease of cutting and fitting
 NEFIT
- Compatible with security tagging systems

S







10mm

FRONT ELEVATION

I2mm

FRONTRUNNER PLUS CUSTOM LOGOS

The positioning of the scraper bars on Frontrunner Entrance Flooring Systems can be varied to allow the incorporation of a logo panel.

Logo panels are achieved by die cutting with another compatible high quality absorbent insert, giving a permanent and colourfast message.

Logo panels run the width of the matwell and are either 30 or 45cm tall, providing a highly visible message in that all important 'first impression' area.

ne content

Frontrunner Entrance Systems incorporating logos can be supplied for recessed systems or surface mounted modular mats.

FRONTRUNNER SB+

Surface mounted 'scrape, clean and dry' entrance flooring system


Frontrunner SB+ is the perfect flooring solution for applications that require an entrance matting with effective drying properties, but do not have a recessed matwell. Its 6mm height, solid backing and absorbent inserts allow it to deliver this.

Frontrunner SB+'s ribbed pattern scrapes dirt off shoes, which is effectively contained by its solid back, whilst the absorbent inserts remove moisture at the entrance.

The hollow ribbed construction makes it light to handle during installation, yet sturdy enough to be heel and wheel proof.

Due to Frontrunner SB+'s lesser overall weight, we recommend adhering it to the sub-floor in high volume traffic areas.


Standard colour



BLACK WITH EXCELLENCE 607 INSERT

PRODUCT	HEIGHT	WEIGHT	STANDARD	ROLL SIZES
Frontrunner SB+	6/8mm	6.3 kg/m ²	10m x 1m	20m x Im
To ensure maximu	ım flexibility a	nd convenience, F	rontrunner Entrand	ce System can be

delivered in rolls or cut to size - ask your salesperson for details.





ACTUAL SIZE: SIDE ELEVATION




Frontrunner SB+




DESIGN COMBINATIONS

Frontrunner Plus is available in a choice of 5 grid colours and 17 co-ordinating absorbent insert colours (see page 23 for full specifications). Shown below is each absorbent insert swatch with the most popular grid choice and the 4 alternative grid colours available.



Colour range shown above may therefore be subject to variation, please check selected carpet insert colour(s) prior to ordering. Due to limitations of the printing process, actual colours shown may vary. All carpet insert colours are subject to manufacturing availability.

This choice of 5 grid colours and 17 insert options provides a combination of 85 differing colourways designed to create the optimum choice for today's interior designer and specifier alike.



Dark Grey

Black

Holly Green


Oxford Blue

^{* 80%} wool, 20% nylon and nylon monofilament scrapers.

Ramping


For surface mounted applications to ease wheeled traffic. Available in aluminium with fixing screws and plugs for permanent fixing, or PVC edges for loose lay applications.

Aluminium ramp






Aluminium edging



PVC ramps



Standard flexible PVC edging in 6cm widths



Low profile flexible PVC edging


PVC Connectors

Standard flexible PVC edging in 10cm widths

Used to join large surface mounted installations together (only for Frontrunner Entry and Frontrunner XT).

'Side to Side' Clip Push fit connector:


ish fit nnector:



'Snap Track' Integral welded flexible vinyl 'Snap Track' for joining panels together: Available in 14mm and 10mm heights.

14 mm 10 mm (lo

120 cm 150 cm 200 cm



SURFACE MODULES

height 14mm

Modules

Frontrunner modules can be positioned in minutes and are available in three standard sizes as shown below, in a range of colours with factory fitted ramped edging to four sides.

PRODUCT	HEIGHT	SI	ZE OPTIONS (d	:m)
Frontrunner Entry	I4mm	80 x 120	100 x 150	110 x 200
Frontrunner Plus	l6mm	80 x 120	100 x 150	110 x 200
Frontrunner Brush	19mm	80 x 120	100 x 150	110 x 200
Frontrunner Brush Wide	l9mm	80 x 120	100 x 150	110 x 200


80 cm 100 cm 110 cm

RECESSED ANCILLARIES

Recessed Mat Frames

For recessed applications, a full range of frames and dividers are purpose designed to provide level and smooth transitions and are simple to install during actual entrance fit out. For full details visit www.frontrunnerplus.com/frontrunner_installation.php








Aluminium frames are available in natural anodised finish. For design elegance and colour continuity, the U, R and T frames are also available in dark grey and black. Edge J, in rigid PVC, is available in Dark Grey or Black.


SPECIFICATIONS & DATA

Sizes & Weights


(all dimensions are nominal)

PRODUCT Rolls	LENGTH (m)	HEIGHT (mm)		WIDTHS (cm)		WEIGHT (kg/m²)
Tolerances	0 + 0.3	+/- 0.5		0/+2		
Frontrunner Brush	10	14/19	60	91		12.7
Frontrunner Brush	5	14/19			120	12.7
Frontrunner Brush Wide	10	14/19	60	91		7.5
Frontrunner Brush Wide	5	14/19			120	7.5
Frontrunner Entry or XT	10	14	60	91		10.5
Frontrunner Entry or XT	5	14			120	10.5
Frontrunner Entry - Low Profile	10	10	60	91		8.7
Frontrunner Entry - Low Profile	5	10			120	8.7
Frontrunner Plus	10	14/16	60	91		10.5
Frontrunner Plus	5	14/16			120	10.5
Frontrunner Plus - Low Profile	10	10/12	60	91		8.7
Frontrunner Plus - Low Profile	5	10/12			120	8.7
Frontrunner SB	10	6		100		6.3
Frontrunner SB	20	6	ĺ	100		6.3
Frontrunner SB+	10	6/8		100		6.3
Frontrunner SB+	20	6/8	1	100		6.3















Frontrunner Entry

Frontrunner SB

Frontrunner XT

Frontrunner Plus



Frontrunner Brush



General Specification

Frontrunner Brush Wide

APPEARANCES	 Frontrunner Entry and Frontrunner XT: Open grid "heelproof" design. Frontrunner Plus: Open grid "heelproof" design with absorbent inserts. Frontrunner Brush: Open grid 'heelproof' design with nylon brush inserts. Frontrunner Brush Wide: Wide spaced open grid design with nylon brush inserts. Frontrunner SB: Open ribbed "heel proof" design on vinyl sheet. Frontrunner SB+: Open ribbed "heel proof" design with absorbent inserts on vinyl sheet.
COLOURS	PVC Grid: Black, Dark Grey, Dark Brown, Holly Green and Oxford Blue homogenous stable colours. Absorbent Inserts: 17 colour choices. See pages 18-19 or visit www.frontrunnerplus.com/downloads/FR_colours.pdf
DURABILITY	PVC Grid: All welded durable construction for long effective use.
INSTALLATION	Recessed wells: www.frontrunnerplus.com/downloads/Installation_Guide_Recessed.pdf Surface mounted applications: www.frontrunnerplus.com/downloads/Installation_Guide_Surface.pdf Framing, Edging and Ramp edging available. See pages 20-21.
WORKABILITY	Available in rolls or cut to size for ease of installation. Flexible vinyl construction is easy to trim and shape on site.
USES	Entrance Flooring Systems for Retail, Hospitality, Offices, Restaurants, Leisure, Industrial, Education, high volume commercial applications etc.

Technical Data

ACOUSTIC	PVC Grid: Excellent sound absorption properties.
CHEMICAL	PVC Grid: Resistant to most acids, alkalines and oils. For specific chemical resistances, see http://www.plastexmatting.com/matfax/doc.php?doc_id=154&action=inline

COMPOSITION PVC Grid: Flexible (DINP plasticised) polyvinyl Chloride.

Absorbent Inserts: see below

	Green & Grey 80/20+	Basalt & Slate	Limestone & Sandstone	301, 3021, 3025, 3031, 3041, 3045, 3051, 3055, 3061, 3071 & 307	Excellence 607
Construction	Twist Pile	Cut Pile	Cut Pile	Tufted, Cut Pile	Tufted, Cut Pile
Pile Content	80% wool, 20% nylon & nylon monofilament	100% nylon	100% nylon	100% nylon	l 00% nylon with nylon monofilament
Pile Weight	1,450 g/m $^{2} \pm 5\%$	$1,000 \text{ g/m}^2 \pm 5\%$	$1,000 \text{ g/m}^2 \pm 5\%$	700 g/m ² \pm 5%	1,080 g/m $^{2} \pm 5\%$
Pile Height	6 mm approx	7 mm (Basalt) 6 mm (Slate)	6 mm	± 6.9 mm	± 6.5 mm
Total Insert Weight*	4,700 g/m² approx			± 3,820 g/m²	4,260 g/m ² \pm 5%
Total Insert Height*	8 mm approx	10 mm (Basalt) 8 mm (Slate)	8 mm	± 9.0 mm	± 9.7 mm
Primary Backing	Non-woven polyester	Non-woven polyester	Non-woven polyester	Non-woven polyester	Non-woven polyester
Secondary Backing	PVC incorporating stabilisers	PVC incorporating stabilisers	PVC incorporating stabilisers	Vinyl compound	Vinyl compound
Flammability		BS 4790 1972 - Low radius of char NBN S 21-203 - method 3		EN 13501 - 1 Bfl S1	EN 13501 - 1 Cfl S1

* Insert carpet & backing.

Nylon Brush Inserts: see below

Construction	Aligned Tufting	Bristle Diameter	0.3 mm	Insert Thickness	l 2 mm
Bristle Content	Nylon 6.6 Monofilaments	Bristle Height	4.5 mm	Backing	PVC

FIRE	PVC Grid: Flame retardant grade (available on request) - EN 13501 - 1 : 2007 - Bfl - S1				
	Absorbent Inserts: see abo	ve			
	Nylon Brush fibres: UL94 -	V2			
ENVIRONMENT	PVC Grid: Made from post-industrial recycled PVC, always with a minimum content of 30% up to 100%. Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H. [*] in any matting product. All PVC grid products are 100% recyclable. * Registration, Evaluation, Authorisation and restriction of CHemical substances.				
REVERSION	PVC Grid: Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments (refer to www.plastexmatting.com/matfax/doc.php?doc_id=254&action=inline)				
SLIP RESISTANCE	DIN 51130:	Frontrunner Entry / Frontrunner XT	RII, VIO		
	ASTM F 1677 (Dry/Wet):	Frontrunner Entry	0.6/0.6		
THERMAL	PVC Grid: Functional -23°C +60°C (slight size variation may occur at temperature extremes).				
UV LIGHT	PVC Grid: Resistant to PVC degradation.				
WARRANTY	2-4 years. See page 24.				

A comprehensive instruction sheet is supplied with each delivery

The Frontrunner Entrance Flooring System uses a simple but effective framing method, which is installed at the same time as the entrance flooring. As the system is supplied in rolls, the installation is quick and easy and does not require any advance templating. Additional visits to site for fitting the matwell frame when the floor slab is poured are also not required.

A range of frames are utilised where large areas of matting are to be installed. The frames are used to divide, cap and secure ends or form shaped edges where required (see page 21).

The simplicity of Frontrunner Entrance Flooring System allows it to be installed by competent tradesmen. Easy to follow instructions are included with each delivery.

Cleaning Guidance

Frontrunner is also very easy to clean within normal cleaning schedules and doesn't require bespoke cleaning products.

Full cleaning instructions come with Frontrunner when delivered or are available at www.frontrunnerplus.com/frontrunner_cleaning.php

Warranty on Frontrunner Entrance Flooring Systems

Frontrunner entrance flooring systems are very durable and many of the installations shown in this brochure have been in place for over ten years and are still performing with admirable style and service. This applies in large retail centres with all the heavy footfall that implies. That's why we can confidently offer a 2-4 year warranty on all of the Frontrunner range.

Full warranty statement: www.frontrunnerplus.com/downloads/FR_warranty.pdf



-				
G	Franks Emerand	· Pleasing	-	-
And a state of the	INSTAL O	-		
			-	
in the second states			1	
And In Column 2 is a	and the state of t	No. of Concession, name	Contractor of the	
	of the local division of	and some the second		
	-			
PC =	Conception of the local division of the loca	1	122	
NUMPER OF		-		
A DECISION OF THE OWNER.			the states and	- 8
and the second se	Contraction of the	-		- 61
	1	_	-	

PLASTEX MATTING & FLOORING PRODUCT RANGE

Barefoot

and Wetside

Section brochures available:

Workplace

Workplace

Frontrunner Entrance **Flooring System**

3 3

	Why is Entrance Flooring important?		3
	Why Frontrunner Entrance Flooring Syste	em?	3
	Which Entrance Flooring System is right for you?	4	4-5
	Frontrunner Entry	6	- 7
	Frontrunner SB		8
	Frontrunner XT		9
	Frontrunner Brush		10
	Frontrunner Brush Wide		П
	Application Gallery	12 -	13
	Frontrunner Plus	14 -	15
	Frontrunner Plus Custom Logos		16
	Frontrunner SB+		17
	Frontrunner Plus Colourways	18 -	19
ł	Surface Mounted Ancillaries and Modules		20
Ŀ	Recessed Ancillaries		21
	Specifications & Technical Data	22 -	23
	Installation, Cleaning Guidance & Warrant	y	24
	Plastex Full Product Range		25

Specialist

Multi-Purpose

Index

The 45+ products within the Plastex range of matting and flooring offer "A

mat for all reasons". To make it easier for you to choose the right mat for the right reason, we've divided our range into the sections here. Simply pick the section that best suits your

need, and then use the segmentation chart you'll find at the front of each section to help you make your final choice.



www.plastexmatting.com

Head Office:

Plastic Extruders Ltd Russell Gardens, Wickford, Essex SSII 8DN, England Tel: +44 (0) 1268 571116 Fax: +44 (0) 01268 560027 e-mail: sales@plastex.co.uk

Plastex Matting Inc.

120 55th St NE, Fort Payne, Alabama AL 35967, USA Tel: +1 256 845 7725 Fax: +1 256 845 6786 e-mail: sales@plastexmatting.com



0

-

S Schoo

www.frontrunnerplus.com